


CALIBRADORES DE ROSCAS INTERIORES TAPON ROSCADO

UNC / UNF / UNEF

LINEA AMERICANA NORMA ANSI B1.2 - Calidad: 2B



Medida Nominal		Medidas Generales				Medidas Nominales			Tolerancias de Fabricacion				
Ø	Paso	LT	LP	LNP	PASO	Ø Primitivo			Ø Primitivo / +	Ø Exterior 0/+	Paso +/1	Semiáng. < + /-	
						pasa	no pasa		pasa	pasa	no pasa	pasa	
"	h x 1"	mm	mm	mm	mm	μ	μ	μ	μ	μ	μ	μ	'
2	56	81	8.0	4.0	0,4536	1,89	1,961	2,184	5.0	5.0	10	5	30
3	48	81	8.0	4.0	0,5292	2,172	2,247	2,515	5.0	5.0	10	5	30
3	56	81	8.0	4.0	0,4536	2,22	2,291	2,515	5.0	5.0	10	5	30
4	48	81	8.0	4.0	0,6350	2,433	2,517	2,845	5.0	5.0	10	5	20
4	48	81	8.0	4.0	0,5292	2,502	2,581	2,845	5.0	5.0	10	5	18
5	40	83	9.0	4.5	0,6350	2,763	2,847	3,175	5.0	5.0	10	5	20
5	44	83	9.0	4.5	0,5772	2,799	2,88	3,175	5.0	5.0	10	5	20
6	32	83	9.0	4.5	0,7937	2,989	3,083	3,505	7.5	7.5	13	7,5	15
6	40	83	9.0	4.5	0,6350	3,094	3,18	3,505	5.0	5.0	10	7,5	20
8	43	83	9.0	4.5	0,7937	3,694	3,746	4,165	7.5	7.5	13	7,5	15
8	46	83	9.0	4.5	0,7056	3,708	3,8	4,166	5.0	5.0	10	7,5	20
10	24	85	10.0	5.0	1,0583	4,138	4,247	4,826	7.5	7.5	13	7,5	15
10	32	85	10.0	5.0	0,7937	4,31	4,409	4,826	7.5	7.5	13	7,5	15
12	24	85	10.0	5.0	1,0583	4,798	4,91	5,486	7.5	7.5	13	7,5	15
12	28	85	10.0	5.0	0,9070	4,897	5,004	5,486	7.5	7.5	13	7,5	15
1/4.	20	95	12.5	6.3	1,2700	5,524	6,646	6,350	7.5	7.5	13	7,5	15
1/4.	28	95	12.5	6.3	0,9071	5,761	5,87	6,350	7.5	7.5	13	7,5	15
1/4.	32	95	12.5	6.3	0,7937	5,834	5,941	6,350	7.5	7.5	13	7,5	15
5/16 18	18	95	12.5	6.3	1,4110	7,021	7,155	7,937	7.5	7.5	13	7,5	10
5/16 24	24	95	12.5	6.3	1,0583	7,249	7,371	7,937	7.5	7.5	13	7,5	15
5/1 32	32	95	12.5	6.3	0,7937	7,422	7,529	7,937	7.5	7.5	13	7,5	15
3/8 16	16	119	16.0	6.3	1,5875	8,494	8,638	9,525	7.5	7.5	15	7,5	10
3/8 24	24	104	10.0	6.3	1,0583	8,887	8,961	9,525	7.5	7.5	13	7,5	15
3/8 32	32	104	10.0	6.3	0,7937	9,009	9,121	9,525	7.5	7.5	13	7,5	15
7/16 14	14	110	10.0	10.0	1,8143	9,934	10,089	11,112	7.5	7.5	15	7,5	10
7/16 20	20	110	16.0	6.3	1,2700	10,287	10,424	11,112	7.5	7.5	13	7,5	15
7/16 24	24	110	16.0	6.3	1,0583	10,424	10,549	11,112	7.5	7.5	13	7,5	15
7/16 28	28	104	10.0	6.3	0,9070	10,523	10,64	11,112	7.5	7.5	13	7,5	15
1/2 13	13	129	20.0	8.0	1,9538	11,43	11,595	12,700	7.5	7.5	15	7,5	10
1/2 20	20	121	12.5	8.0	1,2700	11,874	12,017	12,700	7.5	7.5	13	7,5	15
1/2 28	28	121	12.5	8.0	0,9070	12,111	12,233	12,700	7.5	7.5	13	7,5	15
9/16 12	12	129	20.0	8.0	2,1167	12,913	13,086	14,288	7.5	7.5	15	7,5	10
9/16 18	18	121	12.5	8.0	1,4110	13,371	13,52	14,288	7.5	7.5	13	7,5	10
9/16 24	24	121	12.5	8.0	1,0583	13,599	13,729	14,288	7.5	7.5	13	7,5	15
5/8 11	11	129	20.0	8.0	2,3091	14,376	14,559	15,875	7.5	7.5	15	7,5	10
5/8 18	18	121	12.5	8.0	1,4110	14,958	15,11	15,875	7.5	7.5	13	7,5	10
5/8 24	24	121	12.5	8.0	1,0583	15,187	15,319	15,875	7.5	7.5	13	7,5	15
3/4 10	10	155	25.0	16	2,5400	17,399	17,595	19,050	7.5	7.5	15	7,5	10
3/4 16	16	140	16.0	10	1,5875	18,019	18,184	19,050	7.5	7.5	15	7,5	10
7/8 14	14	116	16.0	10	1,8143	21,047	22,225	22,225	7.5	7.5	15	7,5	10