


**CALIBRADORES DE ROSCA EXTERIOR REFERENCIA ROSCADA PARA HERRADURA
LINEA AMERICANA NATIONAL NORMA ANSI- ROSCA EXTERIOR Calidad 2 A**



Medida Nominal		Medidas Generales				Medidas Nominales			Tolerancias de Fabricacion				
Ø	Paso	LT	LP	LNP	PASO	Ø Primitivo		Ø Exterior	Ø Primitivo / + 0		Ø Exterior 0/+	Paso +/1	Semiang. < + /-
						pasa	no pasa		pasa	no pasa	pasa		
"	h x 1"	mm	mm	mm	mm	µ	µ	µ	µ	µ	µ	µ	'
2	56	77	4.0	4.0	0,4536	1,874	1,821	2,169	5.0	5.0	10	5.0	30
3	48	77	4.0	4.0	0,5292	2,154	2,096	2,497	5.0	5.0	10	5.0	30
3	56	77	4.0	4.0	0,4536	2,202	2,146	2,497	5.0	5.0	10	5.0	30
4	40	77	4.0	4.0	0,6350	2,413	2,349	2,825	5.0	5.0	10	5.0	20
4	48	77	4.0	4.0	0,5292	2,484	2,423	2,827	5.0	5.0	10	5.0	18
5	40	78	4.5	4.5	0,6350	2,743	2,677	3,155	5.0	5.0	10	5.0	20
5	44	78	4.5	4.5	0,5772	2,781	2,718	3,157	5.0	5.0	10	5.0	20
6	32	78	4.5	4.5	0,7937	2,969	2,898	3,485	7.5	7.5	13	7.5	15
6	40	78	4.5	4.5	0,6350	3,073	3,007	3,485	5.0	5.0	10	7.5	20
8	32	78	4.5	4.5	0,7937	3,627	3,553	4,144	5.0	7.5	13	7.5	20
8	36	78	4.5	4.5	0,7056	3,688	3,617	4,145	7.5	7.5	10	7.5	15
10	24	80	5.0	5.0	1,0583	4,112	4,028	4,800	7.5	7.5	13	7.5	15
10	32	80	5.0	5.0	0,7937	4,287	4,211	4,803	7.5	7.5	13	7.5	15
12	24	80	5.0	5.0	1,0583	4,773	4,686	5,461	7.5	7.5	13	7.5	15
12	28	80	5.0	5.0	0,9070	4,872	4,79	5,461	7.5	7.5	13	7.5	15
1/4	20	80	5.0	5.0	1,2700	5,497	5,403	6,322	7.5	7.5	13	7.5	15
1/4	28	89	6.3	6.3	0,9071	5,735	5,652	6,325	7.5	7.5	13	7.5	15
1/4	32	89	6.3	6.3	0,7937	5,809	5,728	6,324	7.5	7.5	13	7.5	15
5/16	18	89	6.3	6.3	1,4110	6,99	6,888	7,907	7.5	7.5	13	7.5	10
5/16	24	89	6.3	6.3	1,0583	7,221	7,127	7,910	7.5	7.5	13	7.5	15
5/16	32	89	6.3	6.3	0,7937	7,397	7,316	7,913	7.5	7.5	13	7.5	15
3/8	16	100	6.3	6.3	1,5875	8,461	8,349	9,492	7.5	7.5	15	7.5	10
3/8	24	100	6.3	6.3	1,0583	8,809	8,712	9,497	7.5	7.5	13	7.5	15
3/8	32	100	6.3	6.3	0,7937	8,984	8,898	9,500	7.5	7.5	13	7.5	15
7/16	14	100	6.3	6.3	1,8143	9,898	9,779	11,077	7.5	7.5	15	7.5	10
7/16	20	100	6.3	6.3	1,2700	10,254	10,147	11,079	7.5	7.5	13	7.5	15
7/16	24	100	6.3	6.3	1,0583	10,396	10,299	11,084	7.5	7.5	13	7.5	15
7/16	28	100	6.3	6.3	0,9070	10,495	10,404	11,085	7.5	7.5	13	7.5	15
1/2	13	117	8.0	8.0	1,9538	11,392	11,265	12,662	7.5	7.5	15	7.5	10
1/2	20	117	8.0	8.0	1,2700	11,841	11,732	12,667	7.5	7.5	13	7.5	15
1/2	28	117	8.0	8.0	0,9070	12,083	11,989	12,672	7.5	7.5	13	7.5	15
9/16	12	126	12.5	12.5	2,1167	12,873	12,741	14,247	7.5	7.5	15	7.5	10
9/16	18	117	8.0	8.0	1,4110	13,335	13,221	14,252	7.5	7.5	13	7.5	10
9/16	24	117	8.0	8.0	1,0583	13,569	13,47	14,257	7.5	7.5	13	7.5	15
5/8	11	126	12.5	12.5	2,3091	14,336	14,196	15,834	7.5	7.5	15	7.5	10
5/8	18	117	8.0	8.0	1,4110	14,923	14,803	15,839	7.5	7.5	13	7.5	10
5/8	24	117	8.0	8.0	1,0583	15,157	15,055	15,845	7.5	7.5	13	7.5	15
3/4	10	146	16.0	16.0	2,5400	17,353	17,203	19,004	7.5	7.5	15	7.5	10
3/4	16	134	10.0	10.0	1,5875	17,98	17,854	19,012	7.5	7.5	13	7.5	10
7/8	14	110	10.0	10.0	1,8143	21,007	20,87	22,185	7.5	7.5	15	7.5	10