

--

TAPÓN ROSCADO LINEA BSW y BSF - Norma B. S. - 84 - B.S. 919 MC CALIBRADORES DE ROSCA INTERIOR - TAPÓN ROSCADO
--



Medida Nominal		Medidas Generales				Medidas Nominales			Tolerancias de Fabricacion				
Ø	Paso	LT	LP	LNP	PASO	Ø Primitivo		Ø Exterior	Ø Primitivo		Ø Exterior	Paso +/1	Semiang. < + /- °
						pasa	no pasa		pasa	no pasa	pasa		
"	h x 1"	mm	mm	mm	mm	µ	µ	µ	µ	µ	µ	µ	'
3/32	48	81	8	4	0,5292	2,042	2,107	2,381	5 / 13	8	5 / 13	5	30°
1/8	40	83	9	4,5	0,6350	2,768	2,842	3,175	5 / 15	10	5 / 15	5	20°
5/32	32	83	9	4,5	0,7937	3,46	3,54	3,968	5 / 15	10	5 / 15	7,5	15°
3/16	24	85	10	5	1,0583	4,084	4,173	4,762	5 / 15	10	5 / 15	7,5	15°
1/4	20	95	12,5	6,3	1,2700	5,537	5,636	6,35	5 / 15	10	5 / 15	7,5	15°
5/16	18	95	12,5	6,3	1,4110	7,034	7,141	7,937	5 / 15	10	5 / 15	7,5	10°
3/8	16	110	16	6,3	1,5875	8,509	8,623	9,525	5 / 15	10	5 / 15	7,5	10°
7/16	14	110	16	10	1,8143	9,952	10,074	11,112	5 / 15	10	5 / 15	7,5	10°
1/2	12	129	20	8	2,1167	11,345	11,477	12,7	5 / 15	10	5 / 15	7,5	10°

TAPÓN ROSCADO LINEA BSW y BSF - Norma B. S. - 84 - B.S. 919 NC



Medida Nominal		Medidas Generales				Medidas Nominales			Tolerancias de Fabricacion				
Ø	Paso	LT	LP	LNP	PASO	Ø Primitivo		Ø Exterior	Ø Primitivo		Ø Exterior	Paso +/1	Semiang. < + /- °
						pasa	no pasa		pasa	no pasa	pasa		
"	h x 1"	mm	mm	mm	mm	µ	µ	µ	µ	µ	µ	µ	'
3/32	48	81	8	4	0,5292	2,042	2,139	2,351	8 ;13	5 ;10	8 ; -13	5	30
1/8	40	83	9	4,5	0,635	2,768	2,878	3,145	10;15	8;13	8 ; -15	5	20
5/32	32	83	9	4,5	0,7937	3,46	3,581	3,938	10;15	8;13	8 ; -15	7,5	15
3/16	24	85	10	5	1,0583	4,084	4,216	4,732	10;15	8;13	8 ; -15	7,5	15
1/4	20	95	12,5	6,3	1,27	5,537	5,684	6,32	10;15	8;13	8 ; -15	7,5	15
5/16	18	95	12,5	6,3	1,411	7,034	7,193	7,905	10;15	8;13	8 ; -15	7,5	10
3/8	16	110	16	6,3	1,5875	8,509	8,682	9,489	10;15	8;13	8 ; -15	7,5	10
7/16	14	110	16	10	1,8143	9,952	10,137	11,075	10;15	8;13	8 ; -15	7,5	10
1/2	12	129	20	8	2,1167	11,345	11,539	12,662	10;15	8;13	8 ; -15	7,5	10

TAPÓN ROSCADO ROSCA PARA CAÑOS NORMA B.S. 2779 (BSPP) / ISO 228
--



Medida Nominal		Medidas Generales				Medidas Nominales			Tolerancias de Fabricacion				
Ø	Paso	LT	LP	LNP	PASO	Ø Primitivo		Ø Exterior	Ø Primitivo		Ø Exterior	Paso +/1	Semiang. < + /- °
						pasa	no pasa		pasa	no pasa	pasa		
"	h x 1"	mm	mm	mm	mm	µ	µ	µ	µ	µ	µ	µ	'
1/8	28	104	10	6,3	0,907	9,147	9,253	9,728	5 ; 15	10	5 ; 15	7,5	15
1/4	19	121	12	8	1,337	12,301	12,425	13,157	5 ; 18	13	5 ; 18	7,5	15
3/8	19	140	16	10	1,337	15,806	15,933	16,662	5 ; 18	13	5 ; 18	7,5	15
1/2	14	116	16	10	1,814	19,793	19,935	20,955	5 ; 18	13	5 ; 18	7,5	10
5/8	14	133	20	12,5	1,814	21,749	21,891	22,911	5 ; 18	13	5 ; 18	7,5	10
3/4	14	133	20	12,5	1,814	25,281	25,433	26,441	5 ; 18	13	5 ; 18	7,5	10
1	11	153	25	16	2,309	31,77	31,935	33,249	5 ; 18	13	5 ; 18	7,5	10