

CALIBRADORES DE ROSCA EXTERIOR REFERENCIA ROSCADA PARA HERRADURA
LINEA BSW y BSF - Norma B.S. 84 - B.S. 919 - Medium Class



Medida Nominal		Medidas Generales				Medidas Nominales			Tolerancias de Fabricacion				
Ø	Paso	LT	LP	LNP	PASO	Ø Primitivo		Ø Exterior	Ø Primitivo		Ø Exterior	Paso +/1	Semiang. < + /-
									/ +	0	0/+		
						pasa	no pasa	pasa	pasa	no pasa	pasa		
"	h x 1"	mm	mm	mm	mm	µ	µ	µ	µ	µ	µ	µ	'
1/8	28	100	6.3	6.3	0,907	9,147	9,039	9,728	10;15	8 ;13	8 ; -15	7,5	15
1/4	19	117	8.0	8.0	1,337	12,301	12,177	13,157	15;20	10;15	10 ; -18	7,5	15
3/8	19	134	10.0	10.0	1,337	15,806	15,679	16,662	15;20	10;15	10 ; -18	7,5	15
1/2	14	110	10.0	10.0	1,814	19,793	19,651	20,955	15;20	10;15	10 ; -18	7,5	10
5/8	14	125	12.5	12.5	1,814	21,749	21,607	22,911	15;20	10;15	10 ; -18	7,5	10
3/4	14	125	12.5	12.5	1,814	25,281	25,128	26,441	15;20	10;15	10 ; -18	7,5	10
1	11	144	16.0	16.0	2,309	31,77	31,605	33,249	15;20	10;15	10 ; -18	7,5	10