


Calibradores de rosca conica ISO R7 (BSPT) TAPONES



Medida Nominal		medidas generales					tolerancias de fabricacion				
Ø	Paso	L	LT	c	d	e	c +/-	e 0/-	Paso +/-	Cono.+/-0	Semiang. < + /-
"	h x 1"	mm	mm	mm	mm	mm	µ	µ	µ	µ	'
1/8'	28	10	89	7,371	1,133	2,266	127	25	7,5	7,5	25'
1/4"	19	20	113	11,023	1,671	3,342	127	25	7,5	10	20'
3/8"	19	16	119	11,361	1,671	3,342	127	25	7,5	10	20'
1/2"	14	25	119	14,965	2,268	4,536	127	25	7,5	15	15'
3/4"	14	20	123	16,327	2,268	4,536	127	25	7,5	15	15'
1"	11	25	140	19,05	2,885	5,77	254	50	10	20	10'

Calibradores de rosca conica ISO R7 (BSPT) HERRADURAS



Medida Nominal		medidas generales				tolerancias de fabricacion				
Ø	Paso	C x B x A(Herradura)	f	g	h	c +/-	e 0/-	Paso +/-	Cono.+/-0	Semiang. < + /-
"	h x 1"	mm	mm	mm	mm	µ	µ	µ	µ	'
1/8'	28	11 x 62,5 x 80	6,69	4,877	1,813	127	25	10	15	30 '
1/4"	19	11 x 62,5 x 80	10,025	7,348	2,672	127	25	10	18	25 '
3/8"	19	11 x 62,5 x 80	10,36	7,686	2,672	127	25	10	18	25 '
1/2"	14	18 x 95 x 133	13,606	9,977	3,627	127	25	10	23	20 '
3/4"	14	18 x 95 x 133	14,968	11,338	3,627	127	25	10	23	20 '
1"	11	18 x 95 x 133	17,318	12,7	4,618	254	50	15	30	15 '