

--

Calidad H6 / H7 s/DIN 7162				
				
Calibres Herradura a pernos cuerpo de Fundición				
CHL	CAMPO	MEDIDAS en mm		
A Pernos	mm	A	B	C
H - 14	0 - 14	68	68	11
H - 26	12 - 26	80	62,5	11
H - 38	24 - 38	92	69,5	11
H - 50	36 - 50	104	78	11

Calibres Herradura yunque cuerpo de Fundición				
CHL	CAMPO	MEDIDAS en mm		
YUNQUE	mm	A	B	C
H - 7D	0 - 7	68	54.0	11
H - 10D	3 - 10	68	54.0	11
H - 16D	9 - 16	80	62,5	11
H - 22D	15 - 22	80	62,5	11
H - 28D	21- 28	92	69,5	11
H - 34D	27 - 34	92	69,5	11
H - 40D	33 - 40	104	78	11
H - 46D	39 - 46	104	78	11

Calibres Herradura a pernos cuerpo de chapa de acero				
CHL	CAMPO	MEDIDAS en mm		
A pernos	mm	A	B	C
H - 75	47 - 75	139	90	10
H - 100	72 - 100	164	109	10
H - 125	97 - 125	189	128	10
H - 150	122 - 150	214	147	10
H - 175	147 - 175	239	166	10
H - 200	172 - 200	264	182	10
H - 225	197 - 225	389	200	10
H - 250	223 - 250	314	217	10
H - 275	247 - 275	339	234	10
H - 300	272 - 300	364	250	10

Calibres Herradura yunque cuerpo de chapa de acero				
CHL	CAMPO	MEDIDAS en mm		
YUNQUE	mm	A	B	C
H - 58D	45 - 59	139	90	10
H - 70D	58 - 72	139	90	10
H - 83D	70 - 84	164	109	10
H - 95D	83 - 97	164	109	10
H - 108D	95 - 109	189	128	10
H - 120D	108 - 122	189	128	10
H - 133D	120 - 134	214	147	10
H - 145D	133 - 147	214	147	10
H - 158D	145 - 159	239	166	10
H - 170D	158 - 172	239	166	10
H - 183D	170 - 184	264	182	10
H - 195D	183 - 197	264	182	10
H - 208D	195 - 209	289	200	10
H - 220D	208 - 222	289	200	10
H - 233D	220 - 234	314	217	10
H - 245D	233 - 247	314	217	10
H - 258D	245 - 259	339	234	10
H - 270D	258 - 272	339	234	10
H - 283D	270 - 284	364	250	10
H - 295D	283 - 297	364	250	10